

# **Ground Line** OGL1 1060

powered by **Elements** 





The OGL1 1060 light line is a minimalistic lighting solution for the design of outdoor areas and public spaces.

Minimally visible housing parts make the luminaire inconspicuous in daylight. At night, the modules can be individually controlled, making it possible to create different lighting scenarios and effects. The vandal-proof housing is impact-resistant and guarantees easy maintenance without tools.

### **Elements LEDs** Homogeneous light for dynamic lighting scenarios




IP69K

Vandal-proof full sealing protects against damage and water



Modular lengths Available in standard lengths of 350, 515 and 1,000 mm that can be arranged in any combination.

Minimal distance between LEDs For a homogeneous lighting effect




29 mm uuluuluuluuluuluul

**Minimalist construction** At just 29 mm wide, the light line can be integrated seamlessly into any architectural concept.

IL | OLG11060 | 04/2021 | 14

### Powered by **Elements**

Elements is the modular technology platform from InstaLighting for maximum demands on lighting quality and flexible planning. A modular system of optics, lamps and control management solutions allows you to configure bespoke high-quality lighting scenarios for every conceivable application.



Freely combinable system of light distributions, light colors and control management modules

Consistent light quality across the entire portfolio for all optics, power classes and light colors.

for ambient temperatures from -20° to +50°C

### Elements optics for diffuse lighting effects Powered by Elements



Placa Disseny, Barcelona



City center König-Heinrich-Platz, Duisburg



Immermannhof-Platz, Düsseldorf



DFB Museum, Dortmund




Stanislawski, Moscow

### Easy-to-install modular system





Can withstand loads and protects the frame from dirt during installation. This makes it easy to adjust the height of the paving to the top edge of the luminaire.




#### 2 Installing the luminaire

After installation, the protective cover is removed and the light inserts can be snapped in without the need for tools. The luminaire fits flush with the surrounding paving.


### System overview OGL2

Powered by **Elements** 





Variant	L (mm)	B (mm)	T (mm)
Ground Line OGL1 106		29	65
Ground Line OGL1 106		29	65
Ground Line OGL1 106	01.000	29	65
Mounting frame	350/515/1.000	109	125
Mounting frame	350/515/1.000	109	165



Various mounting frames for different heights and applications (for example, height-adjustable, installation in concrete, single-flange) available on request.

#### Light colors


Several light colors can be combined in a single luminaire



### System overview OGL11060 Powered by Elements

#### Optics and light distributions

#### Diffuse



#### Maximum Wattage and Luminous flux (Im) for DC 48V und AC 230V

Power Class	Lumen/m						
DC 48V	2.000K	2.700K	3.000K	4.000K	ТW	RGB/3.000K	RGB/Boost Mode
L1: 6W/m	270	430	350	490	490	38, 130, 19	64, 455, 42
L2: 17W/m	700	1.100	1.250	1.250	1.250	96, 331, 48	165, 1.162, 105
AC230V							
L1: 5W/m	150	180	190	200			
L2: 10W/m	410	450	460	480			

#### Freely combinable lengths, optics and light colors

Each module of the OGL1 1060 can be individually controlled, allowing hundreds of conceivable light colors.

Different optics and light colors can be combined and individually controlled in a single luminaire.

Different lengths available on request in modular increments of approx. 8.1 cm

### **Technical data**

Light distribution	diffuse	Lifespan	(L80/B10) (@ 25 °C) 60.000 h
Rated voltage	AC 230 V	Dimmable/controllable	yes
	DC 48 V (for mains adapters	Housing color	stainless steel
	see accessories)	Housing material	stainless steel (V4A)
Protection luminaire	IP68 (2m), IP69, IP69K	Sealing material	plastic   diffuse
Protection class	II for AC 230 V	Glow wire test	650 °C
	III for DC 48 V	Impact resistance	IK10
Color rendering	Ra 92	Druckbelastung	3 metric tons
Ambient temperature	-20 +50 °C	Can be driven over	ja, truck
Storage/transport temper	ature -25 +70 °C		



# Additional lighting solutions from this product familyPowered by ElementsGround line OGL2 with directional lighting effectPowered by Elements



**Ground line OGL2** is based on the same modular system and is therefore freely combinable with ground line OGL1 1060.



Minimalist design - Maximum precision

The ground line OGL2 is a minimalist lighting solution for illuminating facades and architectural elements in outdoor spaces. Minimally visible housing parts make the luminaire inconspicuous in daylight.



## > www.instalighting.de



**Instalighting GmbH** Hohe Steinert 10 58509 Lüdenscheid Germany

T + 49 2351 65619-0 info@instalighting.de