

LEDLUX LX RGBW linear

Light insert



The linear RGBW light insert stands out through its dynamic light and can be integrated into the architecture in a modular fashion. In so doing, the light element fascinates through its precisely controllable coloured light, even light distribution and high-quality white light.

Main Features

- > Modular component system guarantees maximum design flexibility and scalability in the object
- > More than 250,000 product variants provide the right light for every idea
- > Brilliant white light, rich colours and pastel shades from one luminaire by combining RGB and white LED
- > Weatherproof housing for use outdoors
- > Various abstract characteristics make focused illumination possible



IP64

















Product Variations









	Optics	Optics dir.	Max. lumin. flux
LL LX RGBW () C070 ()	Clear	70°	270 lm
LL LX RGBW () G070 ()	Fresnel	70°	270 lm
LL LX RGBW () \$120 ()	Satined	120°	246 lm

Specifications

Lifecycle Status	Active	
Rated voltage DC	28 V SELV	
Power consumption	16.2 W/m	
Degree of protection	IP20 / IP64 (see order code)	
Protection & class	III	
Light colour	RGBW	
Ambient temperature	-20 +45 °C	
Storage/transport temperature	-20 +60 °C	
Service life (L80/B10)	60,000 h	
Length (L)	253 2286 mm	
	,	

Width (B)	20 mm	
Height (H)	21 mm	
Connection mode	See order code	
Cable length	See order code	
Dimmable/Controllable	Yes	
Interface	LEDTRIX	
Housing material	Plastic	
Cover material	Plastic	
Glow-wire testing	850 °C	
Weight	Approx. 0.2 kg/m	
Impact strength	IK06	

Accessories



Safety sleeve IP67 50900049



Supply unit 0-120 W / AM 58920027



SNT ELI 0-120 W 58916023



SNT ELI 0-57 W 58916030



SNT ELI 0-110 W / 30 V 50930074



SNT ELI 0-9 W Molex plug 3pole 58910003



Flat clamp 81081700



High clamp 81081710



instalight Control LEDTRIX Master 50913000



instalight Vario basic device V2 GR 001



instalight Vario interface module LEDTRIX V2 FM LX 001



DMX-LEDTRIX Gateway 2 channel, built-in 51688014