


instalight 1065 A
Linear facade spot












The linear spot supplies monochrome light with the highest light intensity in the smallest installation space. A range of perfectly matched optics and optional DALI activation make this luminaire a lighting all-rounder for high quality facade lighting.
























































































Main Features

- > Ideal for accent lighting by means of rotationally symmetrical or oval optics
- > Uncompromising use as wallwasher thanks to asymmetrical optics
- > Positive locking cover disk prevents dirt adhesion
- > Mounting bracket can be removed for easy and comfortable assembly
- > Ready to connect with system plug for quick and reliable installation
- > Mounting bracket with graduation for fast and reproducible alignment



Product Variations



				Optics dir.	Max. lumin. flux	Light colour	Connection mode
il_1065_AG_40_DA_830X_L5000_02				40°	4520 lm	3000 K	Free cable end
il_1065_AG_40_DA_830X_S0300_02				40°	4520 lm	3000 K	Plug connector
il_1065_AG_40_DA_840X_S0300_02				40°	4700 lm	4000 K	Plug connector
il_1065_AG_40_DA_840X_L5000_02				40°	4700 lm	4000 K	Free cable end
il_1065_AG_4D_DA_830X_S0300_02				11° x 44°	4560 lm	3000 K	Plug connector
il_1065_AG_4D_DA_830X_L5000_02				11° x 44°	4560 lm	3000 K	Free cable end
il_1065_AG_4D_DA_840X_L5000_02				11° x 44°	4650 lm	4000 K	Free cable end
il_1065_AG_4D_DA_840X_S0300_02				11° x 44°	4650 lm	4000 K	Plug connector
il_1065_AG_29_DA_830X_S0300_02				28°	4800 lm	3000 K	Plug connector
il_1065_AG_29_DA_830X_L5000_02				28°	4800 lm	3000 K	Free cable end
il_1065_AG_29_DA_840X_S0300_02				28°	5000 lm	4000 K	Plug connector
il_1065_AG_29_DA_840X_L1000_02				28°	5000 lm	4000 K	Free cable end
il_1065_AG_5C_DA_830X_L1000_02				11° x 41°	4750 lm	3000 K	Free cable end
il_1065_AG_5C_DA_830X_S0300_02				11° x 41°	4750 lm	3000 K	Plug connector
il_1065_AG_5C_DA_840X_L5000_02				11° x 41°	4950 lm	4000 K	Free cable end
il_1065_AG_5C_DA_840X_S0300_02				11° x 41°	4950 lm	4000 K	Plug connector
il_1065_AG_3D_DA_830X_S0300_02				10° x 12°	4780 lm	3000 K	Plug connector
il_1065_AG_3D_DA_830X_L1000_02				10° x 12°	4780 lm	3000 K	Free cable end
il_1065_AG_3D_DA_840X_S0300_02				10° x 12°	4980 lm	4000 K	Plug connector
il_1065_AG_3D_DA_840X_L1000_02				10° x 12°	4980 lm	4000 K	Free cable end
il_1065_AG_10_DA_830X_L5000_02				10°	5020 lm	3000 K	Free cable end
il_1065_AG_10_DA_830X_S0300_02				10°	5020 lm	3000 K	Plug connector
il_1065_AG_10_DA_840X_L5000_02				10°	5250 lm	4000 K	Free cable end
il_1065_AG_10_DA_840X_S0300_02				10°	5250 lm	4000 K	Plug connector
il_1065_AG_66_DA_830X_L1000_02				66°	4720 lm	3000 K	Free cable end
il_1065_AG_66_DA_830X_S0300_02				66°	4720 lm	3000 K	Plug connector
il_1065_AG_66_DA_840X_S0300_02				66°	4920 lm	4000 K	Plug connector
il_1065_AG_66_DA_840X_L1000_02				66°	4920 lm	4000 K	Free cable end

Specifications

Lifecycle Status	Active
Rated voltage AC	220 V ... 240 V
Mains frequency	50 / 60 Hz
Power consumption	53 W
Power factor	0.99
Power factor λ	0.99
Degree of protection	IP67
Efficiency class	A
Protection class	I
Protection \diamond class	I
Optics	Clear
Ambient temperature	-20°C ... +35°C

Storage/transport temperature	-20 ... +70 °C
Service life (L80/B10)	60,000 h (at 25°C)
Length (L)	920 mm
Width (B)	70 mm
Height (H)	164 mm
Connection mode	Plug connector ('S') / Free cable ends ('L')
Cable length	1 m / 5 m ('L'); 0.3 m ('S')
Dimmable/Controllable	Yes
Housing colour	Silver grey
Housing material	Aluminium
Cover material	Tempered glass
Weight	5.1 kg
Impact strength	IK10 / IK05

Accessories



Y connector RST 230V/DALI
IP67, 10-14 mm
IL LTG 5P YV



Extension cable RST 230 V
DALI 1.0 m
IL LTG 5P VL1



Extension cable RST 230 V
DALI 2.0 m
IL LTG 5P VL2



Extension cable RST 230 V
DALI 5.0 m
IL LTG 5P VL5



Socket RST 230 V/DALI
IP67, 10-14 mm
IL LTG 5P AN BU