



Product features

DALI control device with integrated power supply enables the common brightness control (broadcast) of up to 26 DALI participants without an additional DALI power supply Parallel connection of up to four DALI power potentiometers increases the maximum number of DALI participants to 104 Use of additional DALI power potentiometers as auxiliary units (without connecting the integrated power supply) Switching / dimming by pressing / turning the control knob Storage of basic brightness and switch-on brightness

Technical specifications

Control	Power consumption	Protection class
DALI	2 w	IP20

Ambient temperature	-5 ... +45 ° C
Storage & transport temperature	-25 ... + 70 ° C
Nominal voltage	AC 230 V ~
Nominal frequency	50/60 Hz
Output current	max. 52 mA

Protection class	IP20
Connection type	Screw terminals

Dimensions

Width (B)	Height (H)	Length (L)
70.7 mm	32 mm	70.7 mm

Further product features

Equipment

Due to the constant further development and improvement of LED technology, changes are possible
© InstaLighting GmbH, Technical changes reserved
InstaLighting GmbH, Oststraße 14-16, 59929 Brilon, Deutschland
Telephon: + 49 2351 65619-0, sales@instalighting.de, www.instalighting.de

51167002



Order Code	Description
------------	-------------

Additional Information

www.instalighting.de