



**Product features**

Operation of devices with DALI interface in KNX systems Control of up to 64 DALI devices in a maximum of 32 different groups Up to 64 individually addressable DALI device channels Tunable White: Control of DALI operating devices according to DALI DT8 / TW Integration in DALI emergency lighting systems possible (central battery systems) Calling up and saving a maximum of 16 light scenes and 16 effects Visualization of the operating states of the connected DALI devices Manual operation of the DALI groups possible Staircase lighting function with switch-off warning and operating hours counter.

**Technical specifications**

|                |                          |
|----------------|--------------------------|
| <b>Control</b> | <b>Power consumption</b> |
| KNX / DALI     | typ. 150 mW              |

|                                            |                    |
|--------------------------------------------|--------------------|
| <b>Ambient temperature</b>                 | -5 ... + 45 ° C    |
| <b>Storage &amp; transport temperature</b> | -25 ... + 70 ° C   |
| <b>Nominal voltage</b>                     | AC 110 ... 240 V ~ |
| <b>Nominal frequency</b>                   | 50 ... 60 Hz       |
| <b>Nominal voltage DC</b>                  | DC 110 ... 240 V   |

|                         |                 |
|-------------------------|-----------------|
| <b>Housing material</b> | plastic         |
| <b>Connection type</b>  | Screw terminals |

**Dimensions**

|                  |                   |                   |
|------------------|-------------------|-------------------|
| <b>Width (B)</b> | <b>Height (H)</b> | <b>Length (L)</b> |
| 72 mm            | 62 mm             | 90 mm             |

**Further product features**

# 64544421



## Additional Information

[www.instalighting.de](http://www.instalighting.de)