

Supply unit DC28V with 66W

PSB 28V 15W IP66



Product features

This power supply unit is suitable for the switchable operation of voltage-controlled LED modules. With an output voltage of 28 V, it is able to generate an output power of 15 W. By installing the power supply in a box suitable for outdoor use, it can be ideally installed in different application scenarios and meets the requirements for the IP66 degree of protection.

lifespan	>62,000h
Ambient temperature	-25 ... +50°C
Storage & transport temperature	-40 ... +80°C
nominal voltage	AC 230 VRange: AC 90 - 264VDC 127-370V
Nominal frequency	50/60 HzRange: 47 - 63Hz
Weight	1.15kg
Housing material	metal
Protection class	I.
Protection class	IP67

Connection type	free end of line
-----------------	------------------

Dimensions

Width (B)	Height (H)	Length (L)
68 mm	39 mm	228 mm

Further product features

Due to the constant further development and improvement of LED technology, changes are possible
© InstaLighting GmbH, Technical changes reserved 2.2021
Instalighting GmbH, Instalighting GmbH, Hohe Steinert 10, 58509 Lüdenscheid, Deutschland
Telephon: + 49 2351 65619-0, info@instalighting.de, www.instalighting.de

Supply unit DC28V with 66W

PSB 28V 15W IP66



Additional Information

www.instalighting.de