

dl13 2x2 bl 922 sp cc s 23062025



Product features

DL2 downlights are based on the new technology platform "Elements" from InstaLighting for maximum demands on light quality and flexibility in planning. High-quality lighting tools can be configured for every imaginable application from a modular system of optics, lamps and electronics. Precision micro-reflectors ensure maximum light control in the smallest space and direct the light exactly where it is supposed to. Luminaires with Elements can be dimmed without flickering and offer consistent light quality across the entire portfolio for all optics, performance classes and light colors.

Technical specifications

Protection class			
IP20			
lifespan	L80B10 60,000h @ 25 ° C	Housing material	aluminum
Ambient temperature	+5 ... + 35 ° C	Glow wire resistance	650 ° C
Storage & transport temperature	-25 ... + 70 ° C	Protection class	III
		Protection class	IP20
		Impact resistance	IK06
		Connection type	free end of line
		Color fidelity	SDCM 3
		Colour reproduction	typ. 92
		Installation dimensions length [mm]	95
		Installation dimensions width [mm]	95
		Installation dimensions height [mm]	≥ 50
		Installation dimensions ceiling thickness MIN [mm]	1
		Installation dimensions ceiling thickness MAX [mm]	25

Dimensions

Installation dimensions length	Installation dimensions width	Installation dimensions height
--------------------------------	-------------------------------	--------------------------------

dl13 2x2 bl 922 sp cc s 23062025



95 mm

95 mm

≥ 50 mm

Further product features



Equipment

Order Code	Description	
PSU 1.4A 45W DA 1CH IP20		
PSU 1.4A 50W DA8 2CH IP20		
PSU 0.7A 60W CA 1CH IP20		

Additional Information

www.instalighting.de