

dl3 110 940 16 ip20 21042025



Product features

Recessed directional spotlight, rotatable and swiveling Mounting ring made of sheet steel, powder-coated Heat sink made of extruded aluminum, black anodized Housing made of die-cast aluminum with bayonet lock Safety glass and reflector integrated in the bayonet ring All visible parts powder-coated according to RAL Aluminum reflector, polished and anodized Toolless installation thanks to spring technology excl. LED converter

Technical specifications

Protection class			
IP20			
lifespan	L70B50 50,000h @ 25 ° C	Housing material	Aluminum
Ambient temperature	+5 ... + 35 ° C	Protection class	III
Storage & transport temperature	-25 ... + 70 ° C	Protection class	IP20
Weight	approx. 1.6 kg	Connection type	free end of line
		Color fidelity	SDCM 3
		Colour reproduction	>90
		Installation dimensions diameter [mm]	155
		Installation dimensions height [mm]	150
		Installation dimensions ceiling thickness MIN [mm]	3
		Installation dimensions ceiling thickness MAX [mm]	18

Dimensions

Installation dimensions diameter	Installation dimensions height
155 mm	150 mm

dl3 110 940 16 ip20 21042025



Further product features



Equipment

Order Code	Description
PSU 1.4A 45W DA 1CH IP20	
PSU 1A 50W DA8 2CH IP20	

Additional Information

www.instalighting.de