

ogl2 lx 350 a rgb a1 20062025



Product features

The OGL2 floor line is a minimalist lighting solution for illuminating facades and architectural elements outdoors.

Barely visible parts of the housing make the light almost invisible during the day. At night, the precise microreflectors of the Elements platform from InstaLighting ensure perfect and even light distribution without annoying glare effects. The ground line in the RGB variant is operated with a constant voltage of DC 24 V.

Technical specifications

Protection class

IP68 (2m), IP69, IP69K

lifespan	L80B10 60,000h @ 25 ° C
Ambient temperature	-20 ... + 50 ° C
Storage & transport temperature	-25 ... + 70 ° C
nominal voltage	DC 24 V

Housing material	Stainless steel V4A, clear encapsulation
Glow wire resistance	650 ° C
Protection class	III
Protection class	IP68 (2m), IP69, IP69K
Impact resistance	IK10
Connection type	free end of line
Colour reproduction	typ. 92

Dimensions

Further product features



Equipment

Order Code	Description
------------	-------------

ogl2 lx 350 a rgb a1 20062025



PSU 24V 120W IP67



PSB 24V 2x120W
DMX-LX IP65



OGL ZM 01



DMX-LEDTRIX
Gateway EB



OGL F2 350x125



OGL F2 515x125



OGL F2 1000x125



OGL F2 350x165



OGL F2 515x165



ogl2 lx 350 a rgb a1 20062025



OGL F2 1000x165



OGL ZL 03



Additional Information

www.instalighting.de