

Handrail light OHR1 4020 in 230V

ohr1 lh3 n27 710 830x



Product features

The universal light insert made of V4A stainless steel enables highly efficient and contemporary illumination of traffic areas. The fully encapsulated LED light element can be integrated almost invisibly into handrail systems and provides uniform light distribution with high quality of light. This light insert also impresses with its direct connection to the mains voltage and compatibility with standard dimmers.

Technical specifications

Protection class

IP67, IP69, IP69K

Lifespan	L80B10 60,000h @ 25 ° C
Ambient temperature	-20 ... + 45 ° C
Storage & transport temperature	-25 ... + 70 ° C
Nominal voltage	AC 220 ... 240 V
Nominal frequency	50 Hz

Housing material	Stainless steel V4A
Glow wire resistance	650 ° C
Protection class	II
Protection class	IP67, IP69, IP69K
Impact resistance	IK10
Connection type	Crimp connector
Color fidelity	SDCM 3
Colour reproduction	>90
Installation dimensions width [mm]	27
Installation dimensions height [mm]	30

Dimensions


Installation dimensions width	Installation dimensions height
27 mm	30 mm

Handrail light OHR1 4020 in 230V



ohr1 lh3 n27 710 830x



Further product features



Equipment

Order Code	Description	
IL 4020 P 070 27	Slot lock piece 70 mm	
IL 4020 P 100 27	Slot lock piece 100 mm	

Additional Information

www.instalighting.de