




Product features

The universal light insert made of V4A stainless steel enables highly efficient and contemporary illumination of traffic areas. The fully encapsulated LED light element can be integrated almost invisibly into handrail systems with 27 mm grooves and provides uniform light distribution with high quality of light. Due to the simple and robust design, this light insert can also be used in other fields of application, such as under benches or projections.



Technical specifications

Protection class

IP67, IP69, IP69K

lifespan	L80B10 60,000h @ 25 ° C
Ambient temperature	-20 ... + 45 ° C
Storage & transport temperature	-25 ... + 70 ° C
nominal voltage	DC 28 V

Housing material	Stainless steel V4A
Glow wire resistance	650 ° C
Protection class	III
Protection class	IP67, IP69, IP69K
Impact resistance	IK10
Connection type	Crimp connector
Installation dimensions width [mm]	27
Installation dimensions height [mm]	30

ohr1 lx n27 1035 tw 12062025



Dimensions

Installation dimensions width	Installation dimensions height
27 mm	30 mm

Further product features

IK10

IP67

IP69

IP69K

LED

SDCM 3

V4A

LX

RGB

RGBW

TW

Equipment

Order Code	Description
PSU 28V 20W	
PSU 30V 150W IP67	
PSB 28V 15W IP66	
PSB 24V 60W DB IP66	
PSB 30V 2x150W DA-DW IP65	
IL 4020 P 070 27	

ohr1 lx n27 1035 tw 12062025



IL 4020 P 100 27



Additional Information

www.instalighting.de