


tel% C3%A9fono% 3A+49+2351+65619-0
03062025



Product features

The universal light insert made of V4A stainless steel enables highly efficient and contemporary illumination of traffic areas. The fully encapsulated LED light element can be integrated almost invisibly into handrail systems with 27 mm grooves and provides uniform light distribution with high quality of light. Due to the simple and robust design, this light insert can also be used in other fields of application, such as under benches or projections.



Technical specifications

Protection class			
IP67, IP69, IP69K			
lifespan	L80B10 60,000h @ 25 ° C	Housing material	Stainless steel V4A
Ambient temperature	-20 ... + 45 ° C	Glow wire resistance	650 ° C
Storage & transport temperature	-25 ... + 70 ° C	Protection class	III
nominal voltage	DC 28 V	Protection class	IP67, IP69, IP69K
		Impact resistance	IK10
		Connection type	Crimp connector
		Installation dimensions width [mm]	27
		Installation dimensions height [mm]	30

tel% C3%A9fono% 3A+49+2351+65619-0
03062025



Dimensions

Installation dimensions width	Installation dimensions height
27 mm	30 mm

Further product features



Equipment

Order Code	Description
PSU 28V 20W	
PSU 30V 150W IP67	
PSB 28V 15W IP66	
PSB 24V 60W DB IP66	
PSB 30V 2x150W DA-DW IP65	
IL 4020 P 070 27	

tel% C3%A9fono% 3A+49+2351+65619-0
03062025



IL 4020 P 100 27



Additional Information

www.instalighting.de