

ohr1 In n24 1035 840x 28062025



Product features

The universal light insert made of V4A stainless steel enables highly efficient and contemporary illumination of circulation areas. The fully encapsulated LED lighting element can be integrated almost invisibly into handrail systems and provides uniform light distribution with high light quality. These light inserts are suitable for use in standard handrails with a groove width of 24 mm.


Technical specifications

Protection class			
IP67, IP69, IP69K			
lifespan	L80B10 60,000h @ 25 ° C	Housing material	Stainless steel V4A
Ambient temperature	-20 ... + 45 ° C	Glow wire resistance	650 ° C
Storage & transport temperature	-25 ... + 70 ° C	Protection class	III
nominal voltage	DC 28 V	Protection class	IP67, IP69, IP69K
		Impact resistance	IK10
		Connection type	Crimp connector
		Color fidelity	SDCM 3
		Colour reproduction	typ. 85
		Installation dimensions length [mm]	24
		Installation dimensions height [mm]	24

Dimensions

Installation dimensions length	Installation dimensions height
24 mm	24 mm

Further product features



ohr1 In n24 1035 840x 28062025



Equipment

Order Code	Description
PSU 28V 20W	
PSU 30V 150W IP67	
PSB 24V 60W DB IP66	
PSB 28V 15W IP66	
DCV 090 30 IP66	
PSB 30V 2x150W DA IP65	

Additional Information

www.instalighting.de