

### Product features

The light line system is an ideal tool for effectively accentuating buildings. Mechanically reduced to a minimum of material, the LED light line emphasises the architectural character of the building, but when switched off it blends almost invisibly into the background. The lighting insert also impresses with direct connection of the built-in LEDLUX LH3 luminaires to the mains voltage and compatibility with standard dimmers - flicker-free dimming from 10-100%. Inside the façade line, the LEDLUX LH3 is installed in the C070 profile.

## Technical specifications

### Protection class


IP64 (LEDLUX)

<b>lifespan</b>	L80B10 60,000h @ 25 ° C
<b>Ambient temperature</b>	-20 ... + 45 ° C
<b>Storage &amp; transport temperature</b>	-25 ... + 70 ° C
<b>nominal voltage</b>	AC 220 ... 240 V
<b>Nominal frequency</b>	50 Hz
<b>Weight</b>	2.2 kg / m

<b>Housing material</b>	Stainless steel V2A
<b>Protection class</b>	II
<b>Protection class</b>	IP64 (LEDLUX)
<b>Impact resistance</b>	IK10
<b>Color fidelity</b>	SDCM 3
<b>Colour reproduction</b>	typ. 90

## Dimensions

## Further product features



## Additional Information

[www.instalighting.de](http://www.instalighting.de)