

DL11 VS110.2 100 WH 36 940 DA

28042024



Product features

Recessed directional spotlight, gimbal mounted Installation frame made of sheet steel, powder-coated Heat sink made of extruded aluminum, black anodized Housing made of die-cast aluminum with bayonet lock Safety glass and reflector integrated in the bayonet ring All visible parts powder-coated according to RAL Aluminum reflector, polished and anodized Easy installation through height-adjustable mounting brackets including LED converter


Technical specifications

Protection class	
IP20	
Ambient temperature	+5 ... + 35 ° C
Storage & transport temperature	-25 ... + 70 ° C
nominal voltage	AC 220 ... 240 V
Nominal frequency	50/60 Hz
Weight	3.3 kg
Housing material	aluminum
Protection class	I / II
Protection class	IP20
Color fidelity	SDCM 3
Colour reproduction	typ. 92
Installation dimensions length [mm]	300
Installation dimensions width [mm]	160
Installation dimensions ceiling thickness MIN [mm]	1
Installation dimensions ceiling thickness MAX [mm]	20

Dimensions

Installation dimensions length	Installation dimensions width
300 mm	160 mm

Further product features



DL11 VS110.2 100 WH 36 940 DA
28042024



Additional Information

www.instalighting.de