

Product code2 27052024



Značajke proizvoda

Opis / tekst_razvijatelj Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet. Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet. Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet.

Duis autem vel eum iriure dolor in hendrerit in vulputate velit esse molestie posljedica, vel illum dolore eu feugiat nulla facilisis at vero eros et accumsan et iusto odio dignissim qui blandit praesent luptatum zzril delenit augue dui dolore te feugait. Lorem ipsum dolor sit amet, consetetur adipiscing elit, sed diam nonumy nibh euismod tincidunt ut laoreet dolore magna aliquam erat volutpat.

Ut wisi enim ad minimim veniam, quis nostrud Exercitation ullamcorper suscipit lobortis nisl ut aliquip ex ea commodo posljedica. Duis autem vel eum iriure dolor in hendrerit in vulputate velit esse molestie posljedica, vel illum dolore eu feugiat nulla facilisis at vero eros et accumsan et iusto odio dignissim qui blandit praesent luptatum zzril delenit augue dui dolore te feugait.

Nam liber tempor cum soluta nobis eleifend option congue nihil imperdiet doming id quod mazim placerat facer

Tehničke specifikacije

Klasa zaštite	
IP69	
životni vijek	L80B10 60.000h pri 25 ° C
Sobna temperatura	-20 ... + 50 ° C
Temperatura skladištenja i transporta	-20 ... + 70 ° C
nazivni napon	AC 220 ... 230 V
Nominalna frekvencija	50/60 Hz
težina	5,7 kg
Opterećenje vjetrom	0,12 m²
Materijal za stanovanje	Ekstrudiranje aluminija
Otpor žarne žice	850 ° C
Klasa zaštite	III
Klasa zaštite	IP69
Otpornost na udarce	IK10 +

Product code2 27052024




Vrsta veze	slobodni kraj linije
Vjernost boja	SDCM 1
	SDCM 1
Reprodukcija boja	tip 1000
Ugradbene dimenzije duljina [mm]	100
Ugradbene dimenzije širina [mm]	150
Ugradbene dimenzije visina [mm]	50
Instalacijske dimenzije debljina stropa MIN [mm]	1
Ugradbene dimenzije debljina stropa MAX [mm]	20

Dimenzije

Ugradne dimenzije dužine	Ugradbene dimenzije širina	Dimenzije ugradnje visina
100 mm	150 mm	50 mm

Daljnje značajke proizvoda



Oprema

Order Code	Opis
IL 4020 LK 3000	
IL 4020 LK 10000	
IL 4020 AS1 IP67	
IL 4020 ZL 611 01	

Product code2 27052024



IL 4020 ZL 501 01



IL 4020 ZL 202 01



IL 4020 ZL 201 01



IL LTG 5P VL2



IL LTG 5P VL1



IL LTG 5P AN BU



58924050



81081710



OGL ZL 03



Product code2 27052024



IL 4020 P 100 27



IL LTG 5P VL5



IL LTG 5P YV



Dodatne Informacije

www.instalighting.de